













C72

Handheld RFID Reader

-  Android
-  4G
-  WiFi
-  Bluetooth
-  UHF
-  1D Barcode
-  2D Barcode
-  NFC
-  Camera
-  GPS

Chainway C72 is an Android rugged mobile computer. It features powerful processor, 8000mAh battery and superb UHF RFID capability. It can be equipped with Impinj Indy R2000 (will upgrade to Impinj E710 soon) linearly or circularly polarized antenna. That it can read tags in bulk from long distance enables it to be deployed in asset management, retail, warehousing, fleet management and etc.



Specification

| Performance | |
|--------------------------|--|
| Android 8.1 | |
| Operating System | Android 8.1; Soti MobiControl, SafeUEM supported |
| CPU | Cortex-A53 2.5 GHz Octa-core |
| RAM+ROM | 3 GB + 32 GB / 4 GB + 64 GB (optional) |
| Expansion | Supports up to 128 GB Micro SD card |
| Android 11.0 | |
| Operating System | Android 11.0; Soti MobiControl, SafeUEM supported |
| CPU | Cortex-A53 2.3 GHz Octa-core |
| RAM+ROM | 3 GB + 32 GB / 4 GB + 64 GB (optional) |
| Expansion | Supports up to 128 GB Micro SD card |
| Communication | |
| Android 8.1 | |
| WLAN | IEEE802.11 a/b/g/n/ac, 2.4G/5G dual-band, internal antenna |
| Bluetooth | Bluetooth v2.1+EDR, 3.0+HS, v4.1+HS |
| GNSS | GPS/AGPS, GLONASS, BeiDou; internal antenna |
| WWAN (China) | 2G: 900/1800 MHz |
| | 3G: WCDMA: B1,B8 CDMA2000 EVDO: BC0 TD-SCDMA: B34,B39 |
| WWAN (Overseas) | 4G: B1,B3,B5,B8,B34,B38,B39,B40,B41 |
| | 2G: 850/900/1800/1900 MHz |
| WWAN (Overseas) | 3G: B1,B2,B4,B5,B8 |
| | 4G: B1,B2,B3,B4,B5,B7,B8,B12,B17,B20,B25,B40,B66 |
| Android 11.0 | |
| WLAN | IEEE802.11 a/b/g/n/ac, 2.4G/5G dual-band, internal antenna |
| Bluetooth | Bluetooth 5.0 |
| GNSS | GPS/AGPS, GLONASS, BeiDou; internal antenna |
| WWAN | 2G: GSM850/GSM900/DCS1800/PCS1900 |
| | 3G: WCDMA: B1/B2/B4/B5/B8 CDMA2000 EVDO: BC0 TD-SCDMA: A/F |
| WWAN | 4G: B1/B2/B3/B4/B5/B7/B8/B12/B17/B20/B28A/B28B/B34/B38/B39/B40/B41 |
| | |
| Physical Characteristics | |
| Dimensions | 164.2 x 80.0 x 24.3 mm / 6.46 x 3.15 x 0.96 in. |
| Weight | 654 g / 23.07 oz. |
| Display | 5.2" IPS FHD 1920 x 1080 |
| Touch Panel | Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported |
| Power | Li-ion, rechargeable, 8000 mAh |
| | Standby: over 500 hours |
| | Continuous use: over 12 hours (depending on user environment) |
| | Charging time: 3-4 hours (with standard adaptor and USB cable) |
| Expansion Slot | 1 slot for SIM card, 1 slot for SIM or TF card |
| Interfaces | USB 2.0 Type-C, OTG, Type-C headphones supported |
| Audio | Speaker, 2 microphones |
| Keypad | 4 front keys, 1 power key, 2 scan keys, 1 multifunctional key |
| Sensors | Gravity sensor, light sensor, proximity sensor |

| User Environment | |
|----------------------|---|
| Operating Temp. | -4 °F to 122 °F / -20 °C to 50 °C |
| Storage Temp. | -40 °F to 158 °F / -40 °C to 70 °C |
| Humidity | 5% RH - 95% RH non condensing |
| Drop Specification | Multiple 1.5 m / 4.9 ft. drops (at least 20 times) to the concrete across the operating temperature range |
| Tumble Specification | 1000 x 0.5 m / 1.64 ft. falls at room temperature |
| Sealing | IP65 per IEC sealing specifications |
| ESD | ±15 KV air discharge, ±6 KV conductive discharge |

| Developing Environment | |
|------------------------|-----------------------------------|
| SDK | Chainway Software Development Kit |
| Language | Java |
| Tool | Eclipse / Android Studio |

| Data Collection | |
|------------------------|---|
| Camera | |
| Camera | 13 MP Autofocus with flash |
| RFID (Optional) | |
| UHF | |
| Engine | CM2000-1 module based on Impinj Indy R2000; CM710-1 module based on Impinj E710 (coming soon) |
| Frequency | 865-868 MHz / 920-925 MHz / 902-928 MHz |
| Protocol | EPC C1 GEN2 / ISO18000-6C |
| Antenna | Circular polarization (4dBi), linear polarization(1.8dBi) |
| Power | 1 W (30 dBm, +5 dBm to +30 dBm adjustable) |
| | 2 W Optional (33 dBm, for Latin America, etc.) |
| R/W range | Up to 15 m (circular polarization, open outdoors, Impinj MR6 tag); up to 7 m (linear polarization, open outdoors) |
| Fastest Read Rate | 900+ tags/sec (circular polarization) |

* Ranges and rates depend on tags and environment

| Barcode Scanning (Optional) | |
|-----------------------------|---|
| 1D Linear Scanner | Zebra: SE965; Honeywell: N4313 |
| 1D Symbologies | UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc. |
| 2D Imager Scanner | Zebra: SE4710 / SE4750 / SE4750MR; Honeywell: N6603 |
| 2D Symbologies | PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc. |

| NFC | |
|-----------|---|
| Frequency | 13.56 MHz |
| Protocol | ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc. |
| Chips | M1 card (S50, S70), CPU card, NFC tags, etc. |
| Range | 2-4 cm |

| Accessories | |
|-------------|-----------------------------|
| Standard | AC Adaptor, USB Cable, etc. |
| Optional | Cradle, Holster , etc. |

* For detailed specification, please check Accessory Guide.

Notice: Product specifications are subject to change without prior notice. / Model: C72UHF / Update Date: 2021-06-23

CHAINWAY®

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: http://www.chainway.net